

SINGLE ROOM HEAT RECOVERY UNIT

ASPIRVELO AIR ECOCOMFORT RF series

- ➔ Ø 160 and 100 mm
- ➔ Wireless control
- ➔ Temperature, humidity and brightness sensors
- ➔ Up to 64 units can be controlled simultaneously
- ➔ Wall mounting
- ➔ Suitable for rooms up to 50 m²
- ➔ Low noise level
- ➔ High efficiency ceramic heat exchanger up to 90%




3
years
guarantee

IP40

Remote
control

IPX4

Heat
recovery unit



DESCRIPTION:

The "ECOCOMFORT-RF" system is composed by one or more single-room high efficiency heat recovery units suitable for exterior walls installation.

Thanks to the ceramic heat exchanger inside the unit, the heat of the extracted air is accumulated in the heat exchanger and released to the air flow in the intake cycle. The unit is equipped with a G3 filter.

Each ventilating unit is equipped with a DC brushless motor with low power consumption controlled by a microprocessor which automatically sets the speed according to the temperature, humidity and light brightness readings of the sensors on board to ensure the best comfort.

Installation options: 1 "Master" unit with its remote control and up to 64 slave / additional units.

The remote control, thanks to its intuitive graphics, allows the user to set and modify the desired operating mode and to verify the setting status.

CHARACTERISTICS:

- Body made in antistatic ABS plastic;
- Max ambient temperature 45°C;
- Compact dimensions and easy to install;
- Remote control with touch key pad and blue LEDs
- Telescopic body to fit every wall thickness;
- External grille easy to install either from indoor or outdoor;
- G3 filter;
- Flow rectifier to grant higher performances, only for 160mm models
- In compliance to UE Reg. 1254/2014

KIT AP19981 and AP19987 include:


- Heat recovery unit with grille;
- RF remote control.

ACCESSORIES AND SPARE PARTS:

- Heat recovery unit with grille;
- External air supply terminal;
- G3 filter.

DIMENSIONS

MODEL	A	B	C	D	E	F	G	H
ECOCOMFORT 160 RF	180	160	530	47	20	190	125	60
ECOCOMFORT SAT 160 RF		160	530					
ECOCOMFORT 100 RF		107	570					
ECOCOMFORT SAT 100 RF		107	570					



* In case of wall thickness less than 280mm cut the telescopic tube to the needed length and use a standard external grille (not supplied with the product)

TECHNICAL FEATURES

CODE	MODEL	Speed	m ³ /h	W	Power supply	dB(A) 1,5 mt
AP19981	ECOCOMFORT 160 RF	V low	28	2,0	230V~ 50Hz	27
		V medium	48	3,8		32
		V high	68	6,6		38
		V sleep	15	na		na
AP19987	ECOCOMFORT 100 RF	V low	8	2,0	230V~ 50Hz	18
		V medium	18	3,8		23
		V high	30	6,6		28
		V sleep	4	na		na

KIT AP19981 and AP19987 include: heat recovery unit, telescopic body, grille and RF remote control

HEAT RECOVERY UNIT

- Ventilating unit with DC motor;
- PVC shockproof telescopic body;
- Ceramic heat exchanger with efficiency >90%;
- G3 filter.
- RF range: 100 mt open air, 30 mt indoor
- Power supply 230V~ 50Hz;
- Brightness and humidity sensors
- Temperature sensor (only Master unit);
- RF range: 100 mt open air, 30 mt indoor
- Splash proof protection class: IPX4




RF REMOTE CONTROL

- Touch keypad
- Feedback through 9 blu leds
- Supply: 2 batteries type CR2032 (included)
- RF range: 100 mt open air, 30 mt indoor
- Protection class IP40;
- Battery operation life: about 18 months (2 x CR2032 included).




OPERATION




REMOTE CONTROL




■ System status request

-  Set mode and fan speed





■ Manual mode setting

-  Air intake (30 minutes temporary mode)
-  Air extraction (30 minutes temporary mode)
-  Alternate air intake / extraction (45 seconds cycle)

■ Automatic mode setting

-  The master ventilating unit regulates automatically adjusts air intake / extract cycles and the fan speed according to the room / ambient conditions according to temperature, humidity and light brightness readings

■ Fan speed setting

-  high speed
-  medium speed
-  low speed
-  minimum speed

ACCESSORIES

SECONDARY HEAT RECOVERY UNIT

- Suitable to ventilate other rooms
- Up to 63 units can be controlled with 1 control unit



CODE	MODEL	Speed	m³/h	W	Power supply	dB(A) 1,5 mt	For use with
AP19982	ECOCOMFORT SAT 160 RF	V low	28	2,0	230V~ 50Hz	27	AP19981
		V medium	48	3,8		32	
		V high	68	6,6		38	
		V sleep	15	nd		nd	
AP19988	ECOCOMFORT SAT 100 RF	V low	8	2,0	230V~ 50Hz	18	AP19987
		V medium	18	3,8		23	
		V high	30	6,6		28	
		V sleep	nd	nd		nd	

KIT AP19982 and AP19988 include: heat recovery unit, telescopic body, grille



G3 SPARE FILTER

CODE	MODEL	For use with
AP19978	Filter FR004	all ECOCOMFORT models



ELECTRICAL SCHEMES

HEAT RECOVERY UNIT



KEY:

- M = Terminal board 230V
- L = Supply wire
- N = Neutral wire

- FC = cable hole
- FV = screw hole